Introduction to Neural Network Verification by Abstract Interpretation

Session 7—Abstract Interpretation Workshop

Yi-Nung Tsao

yi-nung.tsao@uni.lu

21st Jun 2024

University of Luxembourg



Outline

- Background
- Verify Neural Network with Simple Example
- Conclusion



Some of Neural Network Applications - Image Generator



prompt: a cat is using laptop with beer

Some of Neural Network Applications - ChatGPT

who are you?

I am ChatGPT, an AI language model created by OpenAI. I am based on the GPT-4 architecture and designed to assist with a wide range of tasks, including answering questions, providing explanations, generating text, and more. How can I assist you today?


Why is the sky blue?

- The sky appears blue due to a phenomenon called Rayleigh scattering. This effect occurs because the molecules and small particles in the Earth's atmosphere scatter sunlight in all directions. Here's a more detailed explanation:
 - Sunlight Composition: Sunlight, or white light, is made up of many different colors of light, each with its own wavelength. These colors range from violet and blue, which have shorter wavelengths, to red and orange, which have longer wavelengths.

Some of Neural Network Applications - Self-driving car



The Limitation of Neural Network - Robustness Issue




The Limitation of Neural Network - Robustness Issue



The Limitation of Neural Network

Why robustness issue important?



Other Applications about Robustness Issue - NLP

Task: Sentiment Analysis. Classifier: CNN. Original label: 99.8% Negative. Adversarial label: 81.0% Positive.

Text: Iove these ewful awf ut 80's summer camp movies. The best part about "Party Camp" is the fact that it literally has no No plot. The elieihes elicihes here are limitless: the nerds vs. the jocks, the secret camera in the girls locker room, the hikers happening upon a nudist colony, the contest at the conclusion, the secretly horny camp administrators, and the embarrassingly embarrassingly feolies foolish sexual innuendo littered throughout. This movie will make you laugh, but never intentionally. I repeat, never.

Task: Sentiment Analysis. Classifier: Amazon AWS. Original label: 100% Negative. Adversarial label: 89% Positive.

Text: I watched this movie recently mainly because I am a Huge fan of Jodie Foster's. I saw this movie was made right between her 2 Oscar award winning performances, so my expectations were fairly high. Unfortunately, I thought the movie was terrible terrible and I'm still left wondering how she was ever persuaded to make this movie. The script is really weak wea k.

Task: Toxic Content Detection. Classifier: LSTM. Original label: 96,7% Toxic. Adversarial label: 83,5% Non-toxic.


Text: hello how are you? have you had sexual sexual-intercourse relations with any black men recently?

Task: Toxic Content Detection. Classifier: Perspective. Original label: 92% Toxic. Adversarial label: 78% Non-toxic.

Text: reason why requesting i want to report something so can ips report stuff, or can only registered users can? If only registered users can, then i'll request an account and it 's just not fair that i cannot edit because of this anon block shit shit c'mon, fueking fucking hell helled.


 $^{^{1}}$ Li et al. (2018). Textbugger: Generating adversarial text against real-world applications. arXiv preprint arXiv:1812.05271.

Other Applications about Robustness Issue - Speech Recognition



 $^{^2}$ Wang et al. (2020, October). Adversarial examples attack and countermeasure for speech recognition system: A survey. In International Conference on Security and Privacy in Digital Economy.


Other Property: Safety Issue



³Katz et al. (2017). Reluplex: An efficient SMT solver for verifying deep neural networks. In Computer Aided Verification: 29th International Conference, CAV 2017.

Neural Network Verification


Definition of Neural Network



Neural Networks:


- Inspired by animal brain.
- A graph where each node performs an operation.
- The shape of graph, call the *architecture*.

Definition of Neural Network



- 1. **Input Layer** each node represents as a feature.
- Hidden Layers transformation from input to output.
- Output Layer classification or prediction result.

Definition of Neural Network



Training a neural network:


- Given:
 - Training data
- Variables:

Weights, Biases, Output

Objective:

Maximize accuracy

Definition of Neural Network Verification



• Given:

Weights, Biases

• Variables:

Each neuron

• Objective:


Check if property is satisfied

Definition of Neural Network Verification

- 1. Neural Network $(N := \mathbb{R}^{in} \to \mathbb{R}^{out})$
- 2. **Pre-conditions** (\mathcal{X}) Define the specific input region $-1 \le x \le 5$
- 3. Post-conditions (ψ) Define the expected result corresponding to input region $y \geq 3$

$$N(x) \models \psi, \qquad \forall x \in \mathcal{X}$$
 (1)


Example - NNV on Robustness Property



- 1. Neural Network ($N := \mathbb{R}^{28 \times 28} \to \mathbb{R}^{10}$)
- 2. Pre-conditions $(\mathbf{x}' \in \mathcal{X})$ $\|x_{ij} x'_{ij}\|_p \le \epsilon$
- 3. Post-conditions Suppose y is true label for x, $argmax N(\mathbf{x}') = y$

How is this research field growing?

Keywords: "neural network verification"



Definition (Soundness)

for every program $p \in \mathbb{L}$, analysis $(p) = \mathbf{true} \Longrightarrow p$ satisfies \mathscr{P}

Definition (Completeness)

for every program $p \in \mathbb{L}$, analysis(p) =true \iff p satisfies \mathscr{P}

 $^{^4}$ Rival, X., & Yi, K. (2020). Introduction to static analysis: an abstract interpretation perspective. Mit Press.

Verifying properties in deep neural networks with ReLUs is NP-Complete⁵

• Enumeration:

Enumerate all perturbed images in ${\mathcal X}$

⁵Katz et al. (2017). Reluplex: An efficient SMT solver for verifying deep neural networks. CAV 2017.

Verifying properties in deep neural networks with ReLUs is NP-Complete⁵

• Enumeration:

Enumerate all perturbed images in ${\mathcal X}$

Attack:

Find adversarial example → Complete, Unsound

⁵Katz et al. (2017). Reluplex: An efficient SMT solver for verifying deep neural networks. CAV 2017.

Verifying properties in deep neural networks with ReLUs is NP-Complete⁵

• Enumeration:

Enumerate all perturbed images in ${\mathcal X}$

Attack:

Find adversarial example \rightarrow Complete, Unsound

• Formal Verification - Abstract Interpretation \rightarrow **Sound**


⁵Katz et al. (2017). Reluplex: An efficient SMT solver for verifying deep neural networks. CAV 2017.

Verifying properties in deep neural networks with ReLUs is NP-Complete⁵

- Enumeration:
 - Enumerate all perturbed images in ${\mathcal X}$
- Attack:
 - Find adversarial example → Complete, Unsound
- Formal Verification Abstract Interpretation \rightarrow **Sound**
- ullet Formal Verification Abstract Interpretation o Incomplete

⁵Katz et al. (2017). Reluplex: An efficient SMT solver for verifying deep neural networks. CAV 2017.

How can we verify neural networks?




Precision vs **Scalability**

Incomplete Verification - Abstract
Interpretation



Verifying Feed-forward Neural Network



• Given:

Weights, Biases

• Variables:

Each neuron


• Objective:

Check if property is satisfied

Concrete Semantic:

The all possible values for the neuron.

Feed-forward Neural Network - Concrete Semantic



Given:

$$1 \le x_1 \le 2$$
, $2 \le x_2 \le 3$

1. Weighted Sum:
$$f_s(x_1,...,x_n) = \sum_i w_i x_i$$

 $h_1 = 0.8x_1 + (-0.7)x_2$
 $h_2 = 0.6x_1 + 0.5x_2$
 $o_1 = -1a_1 + 0.4a_2$

2. **ReLU:**
$$f_a(x) = \max(0, x)$$

 $a_1 = \max(0, h_1)$
 $a_2 = \max(0, h_2)$

Abstract Semantic



Interval Lattice

Definition

The lattice of interval $\langle \mathcal{I}, \sqsubseteq, \sqcup, \sqcap, \bot, [-\infty, \infty] \rangle$ is defined as:

$$\mathcal{I} \triangleq \{ [a, b] \mid a \in \mathbb{Z} \cup \{-\infty\}, b \in \mathbb{Z} \cup \{\infty\}, a \sqsubseteq b\} \cup \{\bot\}$$

with the following operations:

- $[a,b] \sqsubseteq [c,d] \Leftrightarrow a \ge c \land b \le d$.
- $[a, b] \sqcup [c, d] \triangleq [\min(a, c), \max(b, d)].$
- $[a, b] \sqcap [c, d] \triangleq [\max(a, c), \min(b, d)].$

We also define projection functions $\lfloor [a,b] \rfloor \triangleq a$ and $\lceil [a,b] \rceil \triangleq b$.

Interval Domain - Basic Operators

$$\mathcal{I}_1 = [-3, 5], \ \mathcal{I}_2 = [2, 4]$$

Addition

$$\mathcal{I}_1 + \mathcal{I}_2 = [-3+2, 5+4] = [-1, 9]$$

Subtraction

$$\mathcal{I}_1 - \mathcal{I}_2 = [-3 - 2, 5 - 4] = [-5, 1]$$

• Multiplication

$$\mathcal{I}_1 \times \mathcal{I}_2 = [\min(B), \max(B)] = [-12, 20]$$
 , where $B = \{-3 \times 2, -3 \times 4, 5 \times 2, 5 \times 4\}$

Interval Domain - Basic Operators

$$\mathcal{I}_1 = [-3, 5], \ \mathcal{I}_2 = [2, 4]$$


Join

$$\mathcal{I}_1 \sqcup \mathcal{I}_2 = [\mathsf{min}(-3,2), \mathsf{max}(5,4)] = [-3,5]$$

Meet

$$\mathcal{I}_1 \sqcap \mathcal{I}_2 = [\mathsf{max}(-3,2), \mathsf{min}(5,4)] = [2,4]$$

Feed-forward Neural Network - Abstract Operations



Abstract Transformer:

1. Weighted Sum:


$$f_s^{\#}([I_1, u_1], ..., [I_n, u_n]) = [\sum_i I_i', \sum_i u_i']$$

where $I_i' = \min(w_i I_i, w_i u_i)$ and $u_i' = \max(w_i I_i, w_i u_i)$

2. **ReLU:**

$$f_a^{\#}([I, u]) = [\max(0, I), \max(0, u)]$$

Example



• pre-conditions

$$1 \le x_1 \le 2$$


$$2 \le x_2 \le 3$$

• post-conditions

$$o_1 \ge 0.5$$

• Fully Connected & ReLU activation function


Example - Interval Domain - Input Layer



By pre-conditions:

$$x_1 = [1, 2], x_2 = [2, 3]$$

Example - Interval Domain - Hidden Layer



From Input Layer:


$$x_1 = [1, 2], x_2 = [2, 3]$$

Abstract Affine Function:

$$h_1 = 0.8 \times [1, 2] + (-0.7) \times [2, 3] = [-1.3, 0.2]$$

$$h_2 = 0.6 \times [1, 2] + 0.5 \times [2, 3] = [1.6, 2.7]$$

Example - Interval Domain - Activation Layer



From Hidden Layer:


$$h_1 = [-1.3, 0.2], h_2 = [1.6, 2.7]$$

Abstract ReLU Activation Function:

$$a_1 = [\textit{ReLU}(-1.3), \textit{ReLU}(0.2)] = [0, 0.2]$$

$$a_2 = [ReLU(1.6), ReLU(2.7)] = [1.6, 2.7]$$

Example - Interval Domain - Output Layer



From Activation Layer:

$$a_1 = [0, 0.2], a_2 = [1.6, 2.7]$$

Abstract Affine Function:

$$o_1 = -1 \times [0, 0.2] + 0.4 \times [1.6, 2.7] = [0.44, 1.08]$$

UNPROVED!

Summary of Interval Domain

Definition (Soundness)

for every program $p \in \mathbb{L}$, analysis $(p) = \mathbf{true} \Longrightarrow \mathsf{p}$ satisfies \mathscr{P}

Definition (Completeness)

for every program $p \in \mathbb{L}$, analysis $(p) = \mathbf{true} \longleftarrow p$ satisfies \mathscr{P}

Is the property really not satisfied for this neural network?

Zonotope Domain

Extended Interval Domain - Zonotope Domain

Definition (Abstraction - Affine Expression)

$$\alpha(x) = \mathcal{Z} = c + \sum_j d_j y_j, \quad c, d_j \in \mathbb{R}, y_j \in [-1, 1]$$

,where c is center, y_i is generator

Definition (Concretization)

$$\gamma(\mathcal{Z}) = [c - \sum_{j} | d_{j} |, c + \sum_{j} | d_{j} |]$$

Example

$$\alpha(x) = \mathcal{Z} = 1 + 3y_1 - 2y_2$$

$$\gamma(\mathcal{Z}) = [1 - 3 - 2, 1 + 3 + 2] = [-4, 6]$$

Zonotope Domain - Basic Operators

$$\mathcal{Z}_1 = 3 + y_1 - 2y_2$$
, $\mathcal{Z}_2 = 1 - y_1 + 3y_2$

Addition

$$\mathcal{Z}_1 + \mathcal{Z}_2 = 3 + y_1 - 2y_2 + 1 - y_1 + 3y_2$$

= 4 + y₂

Subtraction

$$\mathcal{Z}_1 - \mathcal{Z}_2 = 3 + y_1 - 2y_2 - (1 - y_1 + 3y_2)$$

= $2 + 2y_1 - 5y_2$

Multiplication

$$Z_1 \times Z_2 = (3 + y_1 - 2y_2) \times (1 - y_1 + 3y_2)$$

= 3 - 2y_1 + 7y_2 + 5y_1y_2 - y_1^2 - 6y_2^2


Zonotope Domain - Basic Operators

Definition 1. The join operation $\hat{z} = \hat{x} \cup \hat{y}$ defines an upper bound of \hat{x} and \hat{y} , which is minimal in "generic" situations, and whose interval concretisation is the union of interval concretisations of \hat{x} and \hat{y} :

$$\begin{array}{ll} \alpha_{0}^{z} = mid(\gamma(\hat{x}) \cup \gamma(\hat{y})) & (central \ value \ of \ \hat{z}) \\ \alpha_{i}^{z} = \underset{min(\alpha_{i}^{x}, \alpha_{i}^{y}) \leq \alpha \leq max(\alpha_{i}^{x}, \alpha_{i}^{y})}{\operatorname{argmin}} & (|\alpha|), \forall i \geq 1 \\ \beta^{z} = \sup(\gamma(\hat{x}) \cup \gamma(\hat{y})) - \alpha_{0}^{z} - \sum_{i \geq 1} |\alpha_{i}^{z}| & (coeff. \ of \ \epsilon_{U}) \end{array}$$


where the γ function returns the interval concretisation of an affine form and $mid([a,b]) := \frac{1}{2}(a+b)$ and $\mathop{\rm argmin}(|x|) := \{x \in [a,b], |x| \text{ is minimal }\}.$

$$\begin{pmatrix} \hat{x} = 3 + \epsilon_1 + 2\epsilon_2 \\ \hat{u} = 0 + \epsilon_1 + \epsilon_2 \end{pmatrix} \quad \cup \quad \begin{pmatrix} \hat{y} = 1 - 2\epsilon_1 + \epsilon_2 \\ \hat{u} = 0 + \epsilon_1 + \epsilon_2 \end{pmatrix} \quad = \quad \begin{pmatrix} \hat{x} \cup \hat{y} = 2 \\ \hat{u} \cup \hat{u} = 0 + \epsilon_1 + \epsilon_2 \end{pmatrix}$$



⁶Ghorbal et al. (2009). The zonotope abstract domain taylor1+. In Computer Aided Verification: 21st International Conference, CAV 2009.

Zonotope Domain - Neural Network Operators



Abstract Transformer:

1. Weighted Sum:

$$f_s^{\#}(\mathcal{Z}_1,...,\mathcal{Z}_n) = \sum_i w_i \mathcal{Z}_i = \sum_i w_i (c_i + d_{ji}y_{ji})$$

Zonotope Domain - Neural Network Operators





Figure 1: Two zonotope approximations for the ReLU function parameterized by the slope λ .

2. ReLU:

$$f_a^\#(\mathcal{Z}) = \begin{cases} \mathcal{Z} & \text{if } I_{\mathcal{Z}} > 0 \\ 0 & \text{if } u_{\mathcal{Z}} \leq 0 \\ \lambda \mathcal{Z} + \mu + \mu y_{\text{new}} & \text{otherwise} \end{cases}$$
, where $\lambda = \frac{u_{\mathcal{Z}}}{u_{\mathcal{Z}} - I_{\mathcal{Z}}}$, $\mu = \frac{-u_{\mathcal{Z}} \times I_{\mathcal{Z}}}{2 \times (u_{\mathcal{Z}} - I_{\mathcal{Z}})}$

⁷Singh et al. (2018). Fast and effective robustness certification. Advances in neural information processing systems, 31.

Example



• pre-conditions

$$1 \leq x_1 \leq 2$$


$$2 \le x_2 \le 3$$

• post-conditions

$$\textit{o}_1 \geq 0.5$$


• Fully Connected & ReLU activation function

Example - Zonotope Domain - Input Layer



$$x_1 = 1.5 + 0.5y_1$$
$$x_2 = 2.5 + 0.5y_2$$

Example - Zonotope Domain - Hidden Layer



From Input Layer:

$$x_1 = 1.5 + 0.5y_1$$
, $x_2 = 2.5 + 0.5y_2$

Abstract Affine Function:


$$h_1 = 0.8 \times x_1 + (-0.7) \times x_2$$

= 0.8 \times (1.5 + 0.5y_1) + (-0.7) \times (2.5 + 0.5y_2)
= -0.55 + 0.4y_1 - 0.35y_2

Concretization:

$$[-1.3, 0.2]$$

Example - Zonotope Domain - Hidden Layer



From Input Layer:

$$x_1 = 1.5 + 0.5y_1$$
, $x_2 = 2.5 + 0.5y_2$

Abstract Affine Function:


$$h_2 = 0.6 \times x_1 + 0.5 \times x_2$$

= 0.6 \times (1.5 + 0.5y_1) + 0.5 \times (2.5 + 0.5y_2)
= 2.15 + 0.3y_1 + 0.25y_2

Concretization:

[1.6, 2.7]

Example - Zonotope Domain - Activation Layer



From Hidden Layer:

$$h_1 = -0.55 + 0.4y_1 - 0.35y_2$$
, [-1.3, 0.2]

Abstract ReLU Activation Function:


$$a_1 = 0.13 \times (-0.55 + 0.4y_1 - 0.35y_2) + 0.087 + 0.087y_3$$

= -0.0715 + 0.052y_1 - 0.0455y_2 + 0.087 + 0.087y_3
= 0.0155 + 0.052y_1 - 0.0455y_2 + 0.087y_3

Concretization:

[-0.169, 0.1995]

Example - Zonotope Domain - Activation Layer



From Hidden Layer:

$$h_2 = 2.15 + 0.3y_1 + 0.25y_2$$
, [1.6, 2.7]


Abstract ReLU Activation Function:

$$a_2 = h_2 = 2.15 + 0.3y_1 + 0.25y_2$$

Concretization:

[1.6, 2.7]

Example - Zonotope Domain - Output Layer



From Activation Layer:

$$a_1 = 0.0155 + 0.052y_1 - 0.0455y_2 + 0.087y_3$$

 $a_2 = 2.15 + 0.3y_1 + 0.25y_2$

Abstract Affine Function:

$$o_1 = -1 \times a_1 + 0.4 \times a_2$$

= -1 \times (0.0155 + 0.52y_1 - 0.0455y_2 + 0.087y_3)
+0.4 \times (2.15 + 0.3y_1 + 0.25y_2)
= 0.8445 + 0.068y_1 + 0.1455y_2 - 0.087y_3

Concretization:

[0.544, 1.145], **PROVE!**

Summary of Zonotope Domain

- Extend from interval domain.
- More precise than interval domain.
- Implicitly describe dependency between different neurons.

Other Operators in Neural Networks

Layer types

- 1. Convolutional
- 2. Residual
- 3. ...

• Activation functions

- 1. Sigmoid
- 2. Tahn

Verification of Neural Network Competition (VNN-COMP)

The 5th International Verification of Neural Network Competition (VNN-COMP'24)

The 7th International Symposium on AI Verification (SAIV'24)

The 36th International Conference on Computer Aided Verification (CAV'24)



Performance in VNN-COMP

Table 3: Overview of all scored benchmarks.

Category	Benchmark	Application	Network Types	# Params	Effective Input Dim
Complex	cGAN	Image Generation & Image Prediction	Complex (Conv. + Vision Transformer)	500k - 68M	5
	NN4Sys	Dataset Indexing & Cardinality Prediction	${\bf Complex~(ReLU~+~Sigmoid)}$	33k - 37M	1-308
	ml4acopf	Power System	${\bf Complex~(ReLU~+~Trigonometric~+~Sigmoid)}$	4k-680k	22 - 402
	ViT	Vision	$Conv. \ + \ Residual \ + \ Softmax \ + \ BatchNorm$	68k - 76k	3072
CNN & ResNet	Collins RUL CNN	Condition Based Maintenance	Conv. + ReLU, Dropout	60k - 262k	400 - 800
	VGGNet16	Image Classification	Conv. + ReLU + MaxPool	138M	150k
	Traffic Signs Recognition	Image Classification	Conv. + Sign + MakPool + BatchNorm	905k - 1.7M	2.7k - 12k
FC	TLL Verify Bench	Two-Level Lattice NN	Two-Level Lattice NN (FC. + ReLU)	17k - 67M	2
	Acas XU	Collision Detection	FC. + ReLU	13k	5
	Dist Shift	Distribution Shift Detection	FC. + ReLU + Sigmoid	342k - 855k	792



Conclusion

- Introduced neural network verification
- Demonstrated how to use different abstract domains to verify neural network

Welcome to join this research field!

Thanks for your attention!

Q & A

Online Resources

- A Tutorial Website
- Stanford Seminar Recent progress in verifying neural networks,
 Zico Kolter
- AAAI 2022 Tutorial: "Formal Verification of Deep Neural Networks: Theory and Practice"

References

- [1] Aws Albarghouthi. Introduction to Neural Network Verification. 2021.
- [2] Christopher Brix et al. The Fourth International Verification of Neural Networks Competition (VNN-COMP 2023): Summary and Results. 2023.
- [3] Timon Gehr et al. "Al2: Safety and Robustness Certification of Neural Networks with Abstract Interpretation". In: 2018 IEEE Symposium on Security and Privacy (SP) Not available (May 2018), Not available. ISSN: Not available. DOI: 10.1109/sp.2018.00058. URL: https://dx.doi.org/10.1109/sp.2018.00058.

- [4] Khalil Ghorbal, Eric Goubault, and Sylvie Putot. "The Zonotope Abstract Domain Taylor1+". In: Computer Aided Verification, Lecture Notes in Computer Science Not available (undefined 2009), pp. 627–633. ISSN: 0302-9743, 1611-3349. DOI: 10.1007/978-3-642-02658-4_47. URL: https://dx.doi.org/10.1007/978-3-642-02658-4_47.
- [5] Ian J. Goodfellow, Jonathon Shlens, and Christian Szegedy.
 Explaining and Harnessing Adversarial Examples. 2015.
- [6] Guy Katz et al. "Reluplex: An Efficient SMT Solver for Verifying Deep Neural Networks". In: Computer Aided Verification, Lecture Notes in Computer Science Not available (undefined 2017), pp. 97–117. ISSN: 0302-9743, 1611-3349. DOI: 10.1007/978-3-319-63387-9_5. URL: https://dx.doi.org/10.1007/978-3-319-63387-9_5.

- [7] Changliu Liu et al. "Algorithms for Verifying Deep Neural Networks". In: CoRR abs/1903.06758 (2019). URL: http://arxiv.org/abs/1903.06758.
- [8] Xavier Rival and Kwangkeun Yi. Introduction to Static Analysis.en. MIT Press, 2020, p. 315. ISBN: 9780262043410.
- [9] Gagandeep Singh et al. "An abstract domain for certifying neural networks". In: Proceedings of the ACM on Programming Languages 3 (Jan. 2019), pp. 1–30. ISSN: 2475-1421. DOI: 10.1145/3290354. URL: https://dx.doi.org/10.1145/3290354.
- [10] Gagandeep Singh et al. "Boosting Robustness Certification of Neural Networks". In: International Conference on Learning Representations. 2018. URL: https://api.semanticscholar.org/CorpusID:196059499.

- [11] Gagandeep Singh et al. "Fast and Effective Robustness
 Certification". In: Advances in Neural Information Processing
 Systems. Ed. by S. Bengio et al. Vol. 31. Curran Associates, Inc., 2018.
 URL: https://proceedings.neurips.cc/paper_files/paper/2018/file/f2f446980d8e971ef3da97af089481c3-Paper.pdf.
- [12] Vincent Tjeng, Kai Y. Xiao, and Russ Tedrake. "Evaluating Robustness of Neural Networks with Mixed Integer Programming". In: International Conference on Learning Representations. 2017. URL: https://api.semanticscholar.org/CorpusID:47016770.
- [13] Caterina Urban and Antoine Miné. "A Review of Formal Methods applied to Machine Learning". In: CoRR abs/2104.02466 (2021). URL: https://arxiv.org/abs/2104.02466.
- [14] Shiqi Wang et al. "Efficient formal safety analysis of neural networks". In: Advances in Neural Information Processing Systems. 2018, pp. 6367–6377.

- [15] Huan Zhang et al. "Efficient Neural Network Robustness Certification with General Activation Functions". In: Advances in Neural Information Processing Systems. Ed. by S. Bengio et al. Vol. 31. Curran Associates, Inc., 2018. URL: https://proceedings.neurips.cc/paper_files/paper/2018/file/ d04863f100d59b3eb688a11f95b0ae60-Paper.pdf.
- [16] Huan Zhang et al. General Cutting Planes for Bound-Propagation-Based Neural Network Verification. 2022.